

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 November 2001 (29.11.2001)

PCT

(10) International Publication Number
WO 01/89848 A1

(51) International Patent Classification⁷: B41J 2/165, 2/21

(21) International Application Number: PCT/AU00/00596

(22) International Filing Date: 24 May 2000 (24.05.2000)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): SILVERBROOK RESEARCH PTY LTD [AU/AU]; 393 Darling Street, Balmain, NSW 2041 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SILVERBROOK, Kia [AU/AU]; c/o Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, NSW 2041 (AU).

(74) Agent: SILVERBROOK, Kia; c/o Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, NSW 2041 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PRINthead CAPPING ARRANGEMENT



(57) Abstract: A pagewidth inkjet printer is described which includes printhead (11) with a plurality of print nozzles (30) for ejecting ink drops towards a print medium. A space is defined between the nozzles and a nozzle guard (43) with a series of apertures (44) aligned with the nozzles. During printing operation, positive air pressure is supplied to this space, the air exiting the space through the apertures, preventing blockage by paper dust. When not printing, the air supply is closed off by air valve member (66) and a capping member (80) on a rotary platen (14) contacts the printhead to maintain a closed atmosphere at the surface of the nozzles, reducing drying of ink on the nozzles.

WO 01/89848 A1

"Printhead Capping Arrangement"

BACKGROUND OF THE INVENTION

The present invention relates to a printhead capping arrangement for a printer.

More particularly, though not exclusively, the invention relates to a printhead capping arrangement for an A4
5 pagewidth drop on demand printhead capable of printing up to 1600 dpi photographic quality at up to 160 pages per minute.

The overall design of a printer in which the arrangement can be utilized revolves around the use of replaceable printhead modules in an array approximately 8 inches (20 cm) long. An advantage of such a system is the ability to easily remove and replace any defective modules in a printhead array. This would eliminate having to scrap an entire printhead
10 if only one chip is defective.

A printhead module in such a printer can be comprised of a "Memjet" chip, being a chip having mounted thereon a vast number of thermo-actuators in micro-mechanics and micro-electromechanical systems (MEMS). Such actuators might be those as disclosed in U.S. Patent No. 6,044,646 to the present applicant, however, there might be other MEMS print chips.

15 The printhead, being the environment within which the printhead capping arrangement of the present invention is to be situated, might typically have six ink chambers and be capable of printing four color process (CMYK) as well as infra-red ink and fixative.

Each printhead module receives ink via a distribution molding that transfers the ink. Typically, ten modules butt together to form a complete eight inch printhead assembly suitable for printing A4 paper without the need for scanning movement of the printhead across the paper width.
20

The printheads themselves are modular, so complete eight inch printhead arrays can be configured to form printheads of arbitrary width.

Additionally, a second printhead assembly can be mounted on the opposite side of a paper feed path to enable double-sided high speed printing.

25 CO-PENDING APPLICATIONS

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention simultaneously with the present application:

NPA001, NPA002, NPA004, NPA005, NPA006, NPA007, NPA008, NPA009, NPA010, NPA012, NPA016,
NPA017, NPA018, NPA019, NPA020, NPA021, NPA030, NPA035, NPA048, NPA075, NPB001, NPB002,
30 NPK002, NPK003, NPK004, NPK005, NPM001, NPM002, NPM003, NPM004, NPP005, NPP006, NPP016,
NPP017, NPN001, NPP001, NPP003, NPP007, NPP008, NPP018, NPS001, NPS003, NPS020, NPT001,
NPT002, NPT003, NPT004, NPX001, NPX003, NPX008, NPX011, NPX014, NPX016, U52, UMS2, MJ10,
MJ11, MJ12, MJ13, MJ14, MJ15, MJ34, MJ47, MJ52, MJ58, MJ62, MJ63, MJ64, MJ65, MJ66, PAK04,
PAK05, PAK06, PAK07, PAK08, PEC01, PEC02, PEC03, PP01, PP02, PP03, PP04, PP07, PP08, PP09, PP10,
35 PP11, PP12, PP13, PP14, PP15, PP16, and PP17.

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding PCT Application Number when available.

40 OBJECTS OF THE INVENTION

It is an object of the present invention to provide an arrangement for reducing of print nozzles during non-use of a printer.

It is another object of the present invention to provide an arrangement for reducing nozzle blockage during non-use, suitable for the pagewidth printhead assembly as broadly described herein.

It is another object of the present invention to provide an arrangement for reducing nozzle blockage for a printhead assembly on which there is mounted a plurality of print chips, each comprising a plurality of MEMS printing devices.

SUMMARY OF THE INVENTION

5 The present invention provides an inkjet printer, including a plurality of print nozzles for selectively ejecting drops of ink towards a print medium passing said nozzles, a space located between said nozzles and said print medium so that ink drops ejected from the nozzles pass through said space, including means for maintaining a closed atmosphere in said space at a surface of said nozzles when said printer is in a non-printing operational mode.

10 Preferably, the space is formed between the nozzles and a nozzle guard, the nozzle guard having a plurality of apertures aligned with the nozzles so that ink drops ejected from the nozzles pass through the apertures to be deposited on the paper or other print medium.

Preferably, the nozzles are arranged in an array extending across at least an A4 pagewidth, the nozzles preferably comprising MEMS devices. Preferably, the nozzles are arranged on a plurality of print modules of the printhead each with a respective nozzle guard and space.

15 Preferably, air valve means shuts off air supply to the spaces when the printer is in a non-printing operational mode.

Preferably, said means for maintaining a closed atmosphere includes capping means sealing against said printhead, being moved into a capping position when said printer is in said non-printing mode.

20 Preferably also, the capping member is located on a rotatable platen member of the printer, and includes a seal member contacting said printhead in a locus surrounding said nozzle guard apertures.

As used herein, the term "ink" is intended to mean any fluid which flows through the printhead to be delivered to a sheet. The fluid may be one of many different coloured inks, infra-red ink, a fixative or the like.

BRIEF DESCRIPTION OF THE DRAWINGS

25 A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings wherein:

Fig. 1 is a front perspective view of a print engine assembly

Fig. 2 is a rear perspective view of the print engine assembly of Fig. 1

Fig. 3 is an exploded perspective view of the print engine assembly of Fig. 1.

Fig. 4 is a schematic front perspective view of a printhead assembly.

30 Fig. 5 is a rear schematic perspective view of the printhead assembly of Fig. 4.

Fig. 6 is an exploded perspective illustration of the printhead assembly.

Fig. 7 is a cross-sectional end elevational view of the printhead assembly of Figs. 4 to 6 with the section taken through the centre of the printhead.

35 Fig. 8 is a schematic cross-sectional end elevational view of the printhead assembly of Figs. 4 to 6 taken near the left end of Fig. 4.

Fig. 9A is a schematic end elevational view of mounting of the print chip and nozzle guard in the laminated stack structure of the printhead

Fig. 9B is an enlarged end elevational cross section of Fig 9A

Fig. 10 is an exploded perspective illustration of a printhead cover assembly.

40 Fig. 11 is a schematic perspective illustration of an ink distribution molding.

Fig. 12 is an exploded perspective illustration showing the layers forming part of a laminated ink distribution structure according to the present invention.

Fig. 13 is a stepped sectional view from above of the structure depicted in Figs. 9A and 9B,

Fig. 14 is a stepped sectional view from below of the structure depicted in Fig. 13.

Fig. 15 is a schematic perspective illustration of a first laminate layer.

Fig. 16 is a schematic perspective illustration of a second laminate layer.

Fig. 17 is a schematic perspective illustration of a third laminate layer.

Fig. 18 is a schematic perspective illustration of a fourth laminate layer.

5 Fig. 19 is a schematic perspective illustration of a fifth laminate layer.

Fig. 20 is a perspective view of the air valve molding

Fig. 21 is a rear perspective view of the right hand end of the platen

Fig. 22 is a rear perspective view of the left hand end of the platen

Fig. 23 is an exploded view of the platen

10 Fig. 24 is a transverse cross-sectional view of the platen

Fig. 25 is a front perspective view of the optical paper sensor arrangement

Fig. 26 is a schematic perspective illustration of a printhead assembly and ink lines attached to an ink reservoir cassette.

Fig. 27 is a partly exploded view of Fig. 26.

15

DETAILED DESCRIPTION OF THE INVENTION

In Figs. 1 to 3 of the accompanying drawings there is schematically depicted the core components of a print engine assembly including the general environment in which the ink distribution structure of the invention can be located. The print engine assembly is typically formed from pressed metal, plastics or other rigid material. Chassis 10 is intended to be mounted within the body of a printer and serves to mount a printhead assembly 11, a paper feed mechanism and other related components within the external plastics casing of a printer.

In general terms, the chassis 10 supports the printhead assembly 11 such that ink is ejected therefrom and onto a sheet of paper or other print medium being transported below the printhead then through exit slot 19 by the feed mechanism. The paper feed mechanism includes a feed roller 12, feed idler rollers 13, a platen generally designated as 14, exit rollers 15 and a pin wheel assembly 16, all driven by a stepper motor 17. These paper feed components are mounted between a pair of bearing moldings 18, which are in turn mounted to the chassis 10 at each respective end thereof.

A printhead assembly 11 is mounted to the chassis 10 by means of respective printhead spacers 20 mounted to the chassis 10. The spacer moldings 20 increase the printhead assembly length to 220mm allowing clearance on either side of 210mm wide paper.

30 The printhead construction is shown generally in Figs. 4 to 8.

The printhead assembly 11 includes a printed circuit board (PCB) 21 having mounted thereon various electronic components including a 64 MB DRAM 22, a PEC chip 23, a QA chip connector 24, a microcontroller 25, and a dual motor driver chip 26. The printhead is typically 203mm long and has ten print chips 27 (Fig. 13), each typically 21mm long. These print chips 27 are each disposed at a slight angle to the longitudinal axis of the printhead (see Fig. 12), with a slight overlap between each print chip which enables continuous transmission of ink over the entire length of the array. Each print chip 27 is electronically connected to an end of one of the tape automated bond (TAB) films 28, the other end of which is maintained in electrical contact with the undersurface of the printed circuit board 21 by means of a TAB film backing pad 29.

40 The preferred print chip construction is as described in US Patent No 6,044,646 by the present applicant. Each such print chip 27 is approximately 21mm long, less than 1mm wide and about 0.3mm high, and has on its lower surface thousands of MEMS inkjet nozzles 30, shown schematically in Figs. 9A and 9B, arranged generally in six lines - one for each ink type to be applied. Each line of nozzles may follow a staggered pattern to allow closer dot spacing. Six corresponding lines of ink passages 31 extend through from the rear of the print chip to transport ink to the rear of each nozzle. To protect the delicate nozzles on the surface of the print chip each print chip has a nozzle guard 43, best seen in

- 4 -

Fig. 9A, with microapertures 44 aligned with the nozzles 30, so that the ink drops ejected at high speed from the nozzles pass through these microapertures to be deposited on the paper passing over the platen 14.

Ink is delivered to the print chips via a distribution molding 35 and laminated stack 36 arrangement forming part of the printhead 11. Ink from an ink cassette 37 (Figs. 26 and 27) is relayed via individual ink hoses 38 to individual ink inlet ports 34 integrally molded with a plastics duct cover 39 which forms a lid over the plastics distribution molding 35. The distribution molding 35 includes six individual longitudinal ink ducts 40 and an air duct 41 which extend throughout the length of the array. Ink is transferred from the inlet ports 34 to respective ink ducts 40 via individual cross-flow ink channels 42, as best seen with reference to Fig. 7. It should be noted in this regard that although there are six ducts depicted, a different number of ducts might be provided. Six ducts are suitable for a printer capable of printing four color process (CMYK) as well as infra-red ink and fixative.

Air is delivered to the air duct 41 via an air inlet port 61, to supply air to each print chip 27, as described later with reference to Figs. 6 to 8, 20 and 21.

Situated within a longitudinally extending stack recess 45 formed in the underside of distribution molding 35 are a number of laminated layers forming a laminated ink distribution stack 36. The layers of the laminate are typically formed of micro-molded plastics material. The TAD film 21 extends from the underside face of the printhead 11, around the rear of the distribution molding 35 to a recess 46 in a respective TAD film recess 47 (Fig. 13) of which a chip housing layer 47 of the laminate is formed. The TAD material 36 is formed in the printed form of individual print chips 27.

The distribution molding, laminated stack 36 and associated components are best described with reference to Figs. 7 to 19.

Fig. 10 depicts the distribution molding cover 39 formed as a plastics molding and including a number of positioning spigots 48 which serve to locate the upper printhead cover 49 thereon.

As shown in Fig. 7, an ink transfer port 50 connects one of the ink ducts 39 (the fourth duct from the left) down to one of six lower ink ducts or transitional ducts 51 in the underside of the distribution molding. All of the ink ducts 40 have corresponding transfer ports 50 communicating with respective ones of the transitional ducts 51. The transitional ducts 51 are parallel with each other but angled acutely with respect to the ink ducts 40 so as to line up with the rows of ink holes of the first layer 52 of the laminated stack 36 to be described below.

The first layer 52 incorporates twenty four individual ink holes 53 for each of ten print chips 27. That is, where ten such print chips are provided, the first layer 52 includes two hundred and forty ink holes 53. The first layer 52 also includes a row of air holes 54 alongside one longitudinal edge thereof.

The individual groups of twenty four ink holes 53 are formed generally in a rectangular array with aligned rows of ink holes. Each row of four ink holes is aligned with a transitional duct 51 and is parallel to a respective print chip.

The underside of the first layer 52 includes underside recesses 55. Each recess 55 communicates with one of the ink holes of the two centre-most rows of four holes 53 (considered in the direction transversely across the layer 52). That is, holes 53a (Fig. 13) deliver ink to the right hand recess 55a shown in Fig. 14, whereas the holes 53b deliver ink to the left most underside recesses 55b shown in Fig. 14.

The second layer 56 includes a pair of slots 57, each receiving ink from one of the underside recesses 55 of the first layer.

The second layer 56 also includes ink holes 53 which are aligned with the outer two sets of ink holes 53 of the first layer 52. That is, ink passing through the outer sixteen ink holes 53 of the first layer 52 for each print chip pass directly through corresponding holes 53 passing through the second layer 56.

The underside of the second layer 56 has formed therein a number of transversely extending channels 58 to relay ink passing through ink holes 53c and 53d toward the centre. These channels extend to align with a pair of slots 59 formed through a third layer 60 of the laminate. It should be noted in this regard that the third layer 60 of the laminate

includes four slots 59 corresponding with each print chip, with two inner slots being aligned with the pair of slots formed in the second layer 56 and outer slots between which the inner slots reside.

The third layer 60 also includes an array of air holes 54 aligned with the corresponding air hole arrays 54 provided in the first and second layers 52 and 56.

5 The third layer 60 has only eight remaining ink holes 53 corresponding with each print chip. These outermost holes 53 are aligned with the outermost holes 53 provided in the first and second laminate layers. As shown in Figs. 9A and 9B, the third layer 60 includes in its underside surface a transversely extending channel 61 corresponding to each hole 53. These channels 61 deliver ink from the corresponding hole 53 to a position just outside the alignment of slots 59 therethrough.

10 As best seen in Figs. 9A and 9B, the top three layers of the laminated stack 36 thus serve to direct the ink (shown by broken hatched lines in Fig. 9B) from the more widely spaced ink ducts 40 of the distribution molding to slots aligned with the ink passages 31 through the upper surface of each print chip 27.

As shown in Fig. 13, which is a view from above the laminated stack, the slots 57 and 59 can in fact be comprised of discrete non-linear spaced slot segments.

15 The top layer 52 of the laminated stack 36 includes an array of ink passages 31 aligned with the print chip 27.

The third layer 60 also includes an array of ink passages 31 aligned with the print chip 27.

20 The TAB film 28 is sandwiched between the fourth and fifth layers 52 and 64, one or both of which can be provided with recesses to accommodate the thickness of the TAB film.

The laminated stack is formed as a precision micro-molding, injection molded in an Acetal type material. It accommodates the array of print chips 27 with the TAB film already attached and mates with the cover molding 39 described earlier.

25 Rib details in the underside of the micro-molding provides support for the TAB film when they are bonded together. The TAB film forms the underside wall of the printhead module, as there is sufficient structural integrity between the pitch of the ribs to support a flexible film. The edges of the TAB film seal on the underside wall of the cover molding 39. The chip is bonded onto one hundred micron wide ribs that run the length of the micro-molding, providing a final ink feed to the print nozzles.

30 The design of the micro-molding allow for a physical overlap of the print chips when they are butted in a line. Because the printhead chips now form a continuous strip with a generous tolerance, they can be adjusted digitally to produce a near perfect print pattern rather than relying on very close toleranced moldings and exotic materials to perform the same function. The pitch of the modules is typically 20.32mm.

35 The individual layers of the laminated stack as well as the cover molding 39 and distribution molding can be glued or otherwise bonded together to provide a sealed unit. The ink paths can be sealed by a bonded transparent plastic film serving to indicate when inks are in the ink paths, so they can be fully capped off when the upper part of the adhesive film is folded over. Ink charging is then complete.

40 The four upper layers 52, 56, 60, 62 of the laminated stack 36 have aligned air holes 54 which communicate with air passages 63 formed as channels formed in the bottom surface of the fourth layer 62, as shown in Figs. 9b and 13. These passages provide pressurised air to the space between the print chip surface and the nozzle guard 43 whilst the printer is in operation. Air from this pressurised zone passes through the micro-apertures 44 in the nozzle guard, thus preventing the build-up of any dust or unwanted contaminants at those apertures. This supply of pressurised air can be turned off to prevent ink drying on the nozzle surfaces during periods of non-use of the printer, control of this air supply being by means of the air valve assembly shown in Figs. 6 to 8, 20 and 21.

- 6 -

With reference to Figs. 6 to 8, within the air duct 41 of the printhead there is located an air valve molding 66 formed as a channel with a series of apertures 67 in its base. The spacing of these apertures corresponds to air passages 68 formed in the base of the air duct 41 (see Fig. 6), the air valve molding being movable longitudinally within the air duct so that the apertures 67 can be brought into alignment with passages 68 to allow supply the pressurized air through the laminated stack to the cavity between the print chip and the nozzle guard, or moved out of alignment to close off the air supply. Compression springs 69 maintain a sealing inter-engagement of the bottom of the air valve molding 66 with the base of the air duct 41 to prevent leakage when the valve is closed.

The air valve molding 66 has a cam follower 70 extending from one end thereof, which engages an air valve cam surface 71 on an end cap 74 of the platen 14 so as to selectively move the air valve molding longitudinally within the air duct 41 according to the rotational positional of the multi-function platen 14, which may be rotated between printing, capping and blotting positions depending on the operational status of the printer, as will be described below in more detail with reference to Figs. 21 to 24. When the platen 14 is in its rotational position for printing, the cam holds the air valve in its open position to supply air to the print chip surface, whereas when the platen is rotated to the non printing position in which it caps off the micro-apertures of the nozzle guard, the cam moves the air valve molding to the valve closed position.

With reference to Figs. 21 to 24, the platen 14 is rotated parallel to the printhead 11. The platen 14 has a right hand end cap 76 and a left hand end cap 75 at respective ends thereof. The platen 14 has a right hand end cap 76 and a left hand end cap 75 at respective ends thereof. The platen 14 has a right hand end cap 76 and a left hand end cap 75 at respective ends thereof.

The platen member 14 has a platen surface 78, which is divided into a series of segments 79, each segment 79 extending along its length, each separated by 120°. During printing, the platen member is rotated so that the platen surface 78 is positioned opposite the printhead so that the platen surface acts as a support for that portion of the paper being printed at the time. When the printer is not in use, the platen member is rotated so that the capping portion 80 contacts the bottom of the printhead, sealing in a locus surrounding the microapertures 44. This, in combination with the closure of the air valve by means of the air valve arrangement when the platen 14 is in its capping position, maintains a closed atmosphere at the print nozzle surface. This serves to reduce evaporation of the ink solvent (usually water) and thus reduce drying of ink on the print nozzles while the printer is not in use.

The third function of the rotary platen member is as an ink blotter to receive ink from priming of the print nozzles at printer start up or maintenance operations of the printer. During this printer mode, the platen member 14 is rotated so that the exposed blotting portion 81 is located in the ink ejection path opposite the nozzle guard 43. The exposed blotting portion 81 is an exposed part of a body of blotting material 82 inside the platen member 14, so that the ink received on the exposed portion 81 is drawn into the body of the platen member.

Further details of the platen member construction may be seen from Figs. 23 and 24. The platen member consists generally of an extruded or molded hollow platen body 83 which forms the platen surface 78 and receives the shaped body of blotting material 82 of which a part projects through a longitudinal slot in the platen body to form the exposed blotting surface 81. A flat portion 84 of the platen body 83 serves as a base for attachment of the capping member 80, which consists of a caper housing 85, a caper seal member 86 and a foam member 87 for contacting the nozzle guard 43.

With reference again to Fig. 1, each bearing molding 18 rides on a pair of vertical rails 101. That is, the capping assembly is mounted to four vertical rails 101 enabling the assembly to move vertically. A spring 102 under either end of the capping assembly biases the assembly into a raised position, maintaining cams 76,77 in contact with the spacer projections 100.

The printhead 11 is capped when not in use by the full-width capping member 80 using the elastomeric (or similar) seal 86. In order to rotate the platen assembly 14, the main roller drive motor is reversed. This brings a reversing

- 7 -

gear into contact with the gear 79 on the end of the platen assembly and rotates it into one of its three functional positions, each separated by 120°.

5 The cams 76, 77 on the platen end caps 74, 75 co-operate with projections 100 on the respective printhead spacers 20 to control the spacing between the platen member and the printhead depending on the rotary position of the platen member. In this manner, the platen is moved away from the printhead during the transition between platen positions to provide sufficient clearance from the printhead and moved back to the appropriate distances for its respective paper support, capping and blotting functions.

10 In addition, the cam arrangement for the rotary platen provides a mechanism for fine adjustment of the distance between the platen surface and the printer nozzles by slight rotation of the platen 14. This allows compensation of the nozzle-platen distance in response to the thickness of the paper or other material being printed, as detected by the optical paper thickness sensor arrangement illustrated in Fig. 25.

15 The optical paper sensor includes an optical sensor 88 mounted on the lower surface of the PCB 21 and a sensor flag arrangement mounted on the arms 89 protruding from the distribution molding. The flag arrangement comprises a sensor flag member 90 mounted on a shaft 91 which is biased by tension spring 92. As paper is fed into the printer, the leading edge of the flag member contacts the paper and the spring 92 causes the flag member to rotate about the shaft 91. The rotation of the flag member is proportional to the thickness of the paper. The optical sensor 88 detects the position of the flag member and provides a signal to the distance compensation mechanism of the platen 14 to adjust the distance between the platen surface and the printer nozzles.

20 Figs. 26 and 27 show attachment of the printer assembly to a replaceable ink cassette 93. Different inks are supplied to the printhead through hoses 94 leading from an array of female ink valves 95 located inside the printer body. The replaceable cassette 93 containing a six compartment ink bladder and corresponding male valve array is inserted into the printer and mated to the valves 95. The cassette also contains an air inlet 96 and air filter (not shown), and mates to the air intake connector 97 situated beside the ink valves, leading to the air pump 98 supplying filtered air to the printhead. A QA chip is included in the cassette. The QA chip mates with a contact 99 located between the ink valves 95 and air intake connector 96 in the printer as the cassette is inserted to provide communication to the QA chip connector 24 on the PCB.

THE CLAIMS

1. An inkjet printer, including a printhead having plurality of print nozzles for selectively ejecting drops of ink towards a print medium passing said nozzles, a space located between said nozzles and said print medium so that ink drops ejected from the nozzles pass through said space, including means for maintaining a closed atmosphere in said space at a surface of said nozzles when said printer is in a non-printing operational mode.
2. An inkjet printer according to claim 1 wherein said space is formed between said nozzles and a nozzle guard.
3. An inkjet printer according to claim 2 wherein said nozzle guard has a plurality of apertures aligned with said nozzles so that ink drops ejected from said nozzles pass through said apertures.
4. An inkjet printer according to claim 1 further including air supply means providing positive air pressure to said space when the printer is in a printing operational mode and discontinuing said air supply when said printer is in said non-printing operational mode.
5. An inkjet printer according to claim 3 wherein said plurality of nozzles are arranged in an array extending across an A4 pagewidth.
6. An inkjet printer according to claim 3 wherein said nozzle guard comprises a plurality of nozzle guard modules.
7. An inkjet printer according to claim 6 wherein said nozzle guard modules are arranged in a row.
8. An inkjet printer according to claim 7 wherein each print module is associated with a respective nozzle guard to define a respective space.
9. An inkjet printer according to claim 8 wherein said air supply means supplies positive air pressure to each said space.
10. An inkjet printer according to claim 3 wherein said means for maintaining a closed atmosphere includes capping means sealing against said printhead.
11. An inkjet printer according to claim 10 wherein said means for maintaining a closed atmosphere further includes means for discontinuing an air supply to said printer.
12. An inkjet printer according to claim 10 wherein said capping means is located on a platen member of said printer, said capping means being moved into a capping position when said printer is in said non-printing operational mode.
13. An inkjet printer according to claim 12 wherein said platen member is rotatable to bring said capping member into said capping position.
14. An inkjet printer according to claim 13 wherein said printhead extends across an A4 pagewidth, and wherein said platen and capping member also extend across said pagewidth.
15. An inkjet printer according to claim 14 wherein said capping member includes a seal member contacting said printhead in a locus surrounding said nozzle guard apertures.

1/22




FIG. 1

2/22




FIG. 2

3/22





FIG. 3

4/22



5/22




FIG. 6

6/22




FIG. 7




FIG. 8

7/22




FIG. 9a




FIG. 9b

8/22




FIG. 10

9/22




FIG. 11

10/22




FIG. 12

11/22




FIG. 13




FIG. 14

12/22




FIG. 15

13/22




FIG. 16

14/22




FIG. 17

15/22




FIG. 18

16/22




FIG. 19

17/22






FIG. 20

18/22



19/22




FIG. 23




FIG. 24

20/22




FIG. 25

21/22




FIG. 26

22/22




FIG. 27

This Page is inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images
problems checked, please do not report the
problems to the IFW Image Problem Mailbox**